

Amendments to the Claims:

This listing of claims replaces all prior versions, and listings, of claims in the application:

1. (currently amended) A device that covers a throughbore and ~~that is adapted to receive a conduit~~, comprising:

a hollow housing having a closed top, a closed back, a pair of side walls formed integrally with said closed top and said closed back, an open bottom, and an open front adapted ~~to abut~~ that abuts against an exterior surface of a wall having said throughbore formed therein;

fastening means for securing said hollow housing to said exterior surface of said wall so that said open front of said hollow housing abuts said exterior surface of said wall;

said closed top, closed back, and said pair of side walls collectively forming a hollow interior when said open front of said hollow housing is disposed in abutting relation to said exterior surface of said wall;

a conduit being disposed in parallel relation to said exterior surface of said wall;

said hollow interior adapted to accommodate a free end of said conduit;

an upper end of said conduit received within said open bottom of said hollow housing;

said conduit having a lumen adapted to accommodate at least one elongate member cable; and

said at least one cable extending through said lumen, through said hollow housing, and through said throughbore;

a port formed in said closed top ~~back~~, ~~said port adapted to receive a sealant that at least partially fills said hollow housing to seal said throughbore;~~

a sealant introduced into said hollow housing through said port;

said sealant surrounding said at least one cable within said hollow housing and said sealant at least partially filling said hollow housing and sealing said throughbore.

2. (original) The device of claim 1, further comprising:

a cap for closing said port;

said cap being removed from said port when said sealant is introduced into said hollow housing;

said cap being placed in closing relation to said port after said sealant has been introduced into said hollow housing.

3. (original) The device of claim 1, said fastening means further comprising:
a first flange formed integrally with a first side wall of said pair of side walls;
said first flange positioned in normal relation to a said first side wall of said pair of side walls and in overlying relation to said exterior surface of said wall when said open front of said main-body hollow housing is disposed in abutting relation to said exterior surface of said wall;
a second flange formed integrally with a second side wall of said pair of side walls;
said second flange positioned in normal relation to said second side wall of said pair of side walls and in overlying relation to said exterior surface of said wall when said open front of said main-body hollow housing is disposed in abutting relation to said exterior surface of said wall;
- a screw-receiving aperture formed in said first flange; and
a screw-receiving aperture formed in said second flange.
4. (original) The device of claim 3, further comprising:
said hollow housing having a "U"-shape when viewed in end view.
5. (original) The device of claim 4, further comprising:
said closed top having a hemispherical appearance when viewed in front elevation.
6. (currently amended) The device of claim 1, further comprising:
said upper end of said conduit having an upper end being press fit into said open bottom of said hollow housing.